



## ARCADAMP - Damp proof paint eliminates damp in bathrooms and basements, Cures and Prevents dampness



### Product Detail

## ELIMINATE DAMP IN BATHROOMS AND BASEMENTS (above ground)

ARCADAMP will **protect your surfaces from problems caused by dampness** such as mold and mildew or efflorescence (saltpetre) and peeling paint.

ARCADAMP **damp proof paint** is a pliolite resin based and cement based paint which will render interior wall surfaces **damp proof**.

Bonding to the substrate our **damp proof paint** ARCADAMP will effectively protect the surface from persisting **damp flaking paint, saltpetre efflorescence and damp musky smells** due to water penetration. Highly resistant to alkalis and micro-porous, it will **protect your wall and prevent water ingress** through the structure while allowing the substrate to breathe. Easy to use, ARCADAMP **damp proof paint** will dry in only 2 hours and **eliminate existing damp**. Used as a preventive product, ARCADAMP damp proof paint will protect your wall surfaces from damage caused by damp.

ARCADAMP damp proof paint treats and protects the porous outer layer of your wall while providing you with a white matt finish decorative in its own right. The washable surface can be left as is or be covered with a topcoat of your choice.

### Advantages

- Ultra durable, resists peeling, blistering and cracking
- Hides damp stains
- Pure white finish
- High coverage, can be left as is with its decorative white matt finish: perfect for a contemporary look and to hide surface imperfections
- Easy to apply
- Can be recoated
- Dries quickly (1-2 hours on the average)
- Will protect your surfaces from problems caused by dampness such as mold and mildew or efflorescence (saltpetre) and peeling paint.
- Microporous, will allow the wall to breathe



- Treats and prevents dampness in your basement or garage, bathroom or cellars
- Damp proof membrane

## Where to apply ?

Arcadamp can be applied to damp plaster or masonry, brick, cement, concrete block...

**IMPORTANT:** Not suitable for underground walls, only above ground. If you need to waterproof an underground wall we recommend our tanking system Arcacem Basement.

## Additional products:

If present, mold, mildew and salpetre must be treated with Arcasaltpetre before applying Arcadamp.

### Application

## Tools:

brush or roller, clean up with white spirit.

## Application Conditions:

Do not apply in temperatures lower than 5°C or higher than 35°C. Avoid application in direct sun and/or strong wind and/or rain.

## Product Preparation

Arcadamp is ready to use, mix carefully before application.

## Surface Preparation

Clean substrate of substances that might interfere with the performance of the damp proof paint.

Remove all dust, dirt, paint, efflorescence (white powdery deposits), mildew and moss, oil, pollution deposits, and other contaminants prior to application.

The surface must be cleaned by thorough wire brushing or pressure washing as necessary to achieve the required surface condition.

Treat the wall for fungus and moss or mildew prior to application with **ARCAMOSS**.

Treat the wall for saltpetre prior to application with **ARCASALTPETRE**

Allow pressure washed surfaces to dry prior to coating. The surface to be treated can be damp upon application but not wet.

Note: Arcadamp is designed to treat unpainted masonry surfaces, any paint present on older surfaces must be removed as much as possible



prior to application.

## How to apply?

Stir material thoroughly before and periodically during application to maintain a homogenous mixture.  
Apply ARCADAMP like a paint and let dry.  
Apply a 2nd coat on very porous surfaces (highly recommended).

## Drying time

Dry to touch (20°C) : 1 to 2 hours  
Recoatable : 12 hours

## Coverage

Up to 4m<sup>2</sup> (square meter) per litre

- 0.75l will cover up to 3m<sup>2</sup> (square meter)
- 2.5l will cover up to 10m<sup>2</sup> (square meter)
- 5l will cover up to 20m<sup>2</sup> (square meter)
- 10l will cover up to 40m<sup>2</sup> (square meter)

Apply 1 or 2 coats depending on the porosity of the substrate (for example, apply 2 coats on porous concrete blocks).

## Storage

Store in unopened containers in a clean, dry area.  
Keep material from freezing and/or extreme heat.

## Video

## Product short description:

A damp proof paint which adheres to all masonry surfaces, ARCADAMP will protect your walls from damp, efflorescence, peeling paint, damp smells.